

COMPARAISON DES APPAREILS - CARACTÉRISTIQUES TECHNIQUES

EAU FROIDE - APPAREIL MURAL OU POSÉ OU SOL

WS 1000 (Page 32-33)		La série WS RP (Page 34-35)							
WS 1000 TS		WS RP 1000 TS		WS RP 1200 TS		WS RP 1400 TS		WS RP 1600 TS	
sans tambour-enrouleur		sans tambour-enrouleur		sans tambour-enrouleur		sans tambour-enrouleur		sans tambour-enrouleur	
30-200 / 3-20		30-200 / 3-20		30-190 / 3-29		30-180 / 3-18		30-150 / 3-15	
230 / 23		240 / 24		210 / 21		200 / 20		170 / 17	
400 / 3 / 50 / 12		400 / 3 / 50 / 14.4 (32A)		400 / 3 / 50 / 14.4 (32A)		400 / 3 / 50 / 14.4 (32A)		400 / 3 / 50 / 14.3 (32A)	
1400		1440		1440		1440		1440	
60		60		60		60		60	
16	960	16	960	19	1140	22	1320	26	1600
7.5	5.5	8.0	6.3	8.0	6.3	8.0	6.3	8.0	6.3
-		-		-		-		-	
-		-		-		-		-	
7.5		7.5		7.5		7.5		7.5	
670 / 430 / 510		670 / 430 / 510		670 / 430 / 510		670 / 430 / 510		670 / 430 / 510	
62		100		100		100		100	
●		●		●		●		●	
●		●		●		●		●	
●		●		●		●		●	
-		-		-		-		-	
-		-		-		-		-	
-		-		-		-		-	
41081	10 (DN 8)	41081	10 (DN 8)	41081	10 (DN 8)	41081	10 (DN 8)	41081	10 (DN 8)
123272	Starlet	123272	Starlet	123272	Starlet	123272	Starlet	123272	Starlet
-	-	-	-	-	-	-	-	-	-
12420-D2505	● D2505	12420-D2505	● D2505	12420-D25065	● D25065	12420-D2508	● D2508	12420-D4011	● D4011
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
13310		13310		13310		13310		13310	
413130		4131400		4131500		4131600		4131700	